

The Cisco Live! logo features the word "CISCO" in a dark blue, sans-serif font, followed by "Live!" in a dark blue, cursive script font. The background of the entire image is a vibrant, multi-colored abstract pattern of overlapping, wavy lines and geometric shapes, transitioning from dark blue on the left to bright yellow and white in the center, and then to various shades of blue and green on the right.

CISCO *Live!*

Let's go



The bridge to possible

Cisco IOS XE & Terraform

How to become an IOS XE Terraform Expert

Story DeWeese, Technical Marketing
@StoryDeWeese

CISCO *Live!*

DEVNET-2464

Infrastructure as Code (IAC) allows us to automate provisioning and management of Cisco Catalyst 9000 devices more efficiently. In this session, automation tooling will be used to programmatically deploy BGP EVPN network fabric. Infrastructure as Code concepts will be demonstrated on the Catalyst 9000 using Terraform. Both enterprise campus and cloud-native use cases and examples will be shared. You'll leave this session with ideas to help you get started with Infrastructure as Code, understand benefits of IAC, and understand more about the Terraform tooling. With IAC and Cisco IOS XE, you can automate any tooling on any interface.


Agenda

- Programmability and Automation
- YANG Suite
- IOS XE Capabilities
- Terraform IOS XE Integration
- Use Case Examples
- Conclusion


Cisco IOS XE Programmability & Automation Lifecycle




Network Engineer



Cisco IOS XE Programmability & Automation Lifecycle



Network Engineer




Network Configuration Protocol (NETCONF), RESTCONF, gNMI

YANG “native” Data Models, OpenConfig,

YANG Suite, Terraform, Ansible, pyATS tooling

IOS XE Programmability & Automation Lifecycle





Model Driven Programmability Interface Comparison

Network architecture, security posture and policy, YANG data modules, tools and language preferences are some considerations when leveraging the various MDP interfaces

	NETCONF	RESTCONF	gNMI
Minimum IOS XE Version	16.6	16.7	16.8
Recommended Version	17.6	17.6	17.7
Default Port	830	443	9339
Operations	<get>,<get-config>,<edit-config>,<establish-subscription>	GET, POST, PUT, PATCH, DELETE	GET, SET, SUBSCRIBE
Encoding	XML	XML or JSON	RFC7951 JSON_IETF
Security	SSH + PKI certificate or password	HTTPS user/pass	TLS certificate with user authentication
Transport Protocol	SSH	HTTPS	HTTP/2
Tooling	YANG Suite, ncclient, Netconf-console	YANG Suite*, Postman, python	YANG Suite*, gnmic, gnmi_cli
Content	YANG	YANG	YANG + Protobuf

IOS XE Programmability and Telemetry “Stack”



CLI

SNMP

WebUI

The NETCONF, RESTCONF, gNMI and gRPC are programmatic interfaces that provide additional methods for interfacing with the IOS XE device – Just like the CLI, SNMP, and WebUI is used for configuration changes and operational metrics so can the programmatic interfaces of NETCONF, RESTCONF, gNMI, and gRPC.

YANG data models define the data that is available for configuration and streaming telemetry






IOS XE - YANG Model Coverage on GitHub

RFC7950 states that “YANG is a data modeling language used to model configuration data, state data, Remote Procedure Calls, and notifications for network management protocols”

YANG module name.yang	Description
Cisco-IOS-XE-native	running-config
Cisco-IOS-XE-{feature}-cfg	Feature configuration
Cisco-IOS-XE-{feature}-oper	Feature operational data
Cisco-IOS-XE-{feature}-rpc	Actions
Cisco-evpn-service	EVPN service abstraction
OpenConfig-{feature}	abstraction for config & oper




<https://github.com/YangModels/yang/tree/master/vendor/cisco/x>

Programmability and Automation



Terraform uses the RESTCONF API on IOS XE



Open-source Infrastructure as Code (IaC) Software Tool providing a consistent CLI workflow to manage hundreds of cloud services. Terraform codifies cloud APIs into declarative configuration files.

Resources:

Ask IOS XE Terraform Provider Webex space:

<https://eurl.io/#PtsT8eJFI>


GitHub Repository:

<https://github.com/CiscoDevNet/terraform-provider-iosxe/>

Provider Documentation:


<https://registry.terraform.io/providers/CiscoDevNet/iosxe/latest>

Terraform uses the RESTCONF API



What's IaC?

Infrastructure as Code (IaC) is the process of managing changes through code, rather than a manual process



Learn more about IaC here:

<https://developer.cisco.com/iac/#:~:text=Adopting%20Infrastructure%20as%20Code%20allows,data%20center%20to%20the%20edge>

IOS XE API Pre-Req

```
Cat9k-1#conf t
Enter configuration commands, one per line.  End with
CNTL/Z.
Cat9k-1 (config) #aaa new-model
Cat9k-1 (config) #aaa authentication login default local
Cat9k-1 (config) #aaa authorization exec default local
Cat9k-1 (config) #username admin privilege 15 password cisco

Cat9k-1 (config) #restconf
```

Enable AAA

Enable RESTCONF

This is the most basic example ☺

There are additional configuration knobs for ACL, AAA, RBAC, etc

Terraform on IOS XE




Terraform Terminology

Terraform uses an execution plan file with a provider and resource definitions.

An **execution plan file** defines the provider and resources. It is written in HashiCorp Configuration Language (HCL), similar to JSON, and stored with a .tf extension

A **provider** is a plugin to make a collection of resources accessible

A **resource** (or infrastructure resource) describes one or more infrastructure objects managed by Terraform. With the IOS XE Terraform provider, resources can be considered the same as a configurable feature



Getting Started with Terraform + IOS XE Provider

1. Enabling the RESTCONF API on the switch

```
Switch# conf t
Switch(config)# restconf
```

2. Install [Terraform](#)

```
$ apt install terraform
```

3. Clone the [IOS XE Terraform Provider](#) GitHub repository

```
$ git clone https://github.com/CiscoDevNet/terraform-provider-iosxe
... or ...
$ https://github.com/jeremycohoe/cisco-ios-xe-dcloud-terraform
```

4. Apply Terraform VLAN example

```
$ terraform init
$ terraform plan
$ terraform apply acl_and_vlan.tf
```

IOS XE Terraform Provider

Documentation and details about the provider are available on the Hashicorp Registry

<https://registry.terraform.io/providers/CiscoDevNet/iosxe/latest>

Source code is in the GitHub Repository: <https://github.com/CiscoDevNet/terraform-provider-iosxe/>

HashiCorp Terraform Registry

Providers / CiscoDevNet / iosxe **Version 0.5.1** Latest Version

iosxe

iosxe Partner by CiscoDevNet

Networking DEVWKS-2461

VERSION 0.5.1 PUBLISHED a month ago SOURCE CODE [CiscoDevNet/terraform-provider-iosxe](https://github.com/CiscoDevNet/terraform-provider-iosxe/)

iosxe provider

> Guides

> AAA

> BFD

> BGP

> CTS

> Crypto

> EVPN

> General

> Interface

> MDT

> MPLS

> Management

> Multicast

> OSPF

> QoS

> Routing

> Switching

> System

> VRF

∨ General

∨ Resources

iosxe_cli

iosxe_restconf

iosxe_save_config

∨ Data Sources

iosxe_restconf

Terraform resource utilizing the CLI RPC

<https://registry.terraform.io/providers/CiscoDevNet/iosxe/latest/docs/resources/cli>

iosxe_cli (Resource)

This resource is used to configure arbitrary CLI commands. This should be considered a last resort in case YANG models are not available, as it cannot read the state and therefore cannot reconcile changes.

Example Usage

```
resource "iosxe_cli" "example" {  
  cli = <<-EOT  
  interface Loopback123  
  description configured-via-restconf-cli  
  EOT  
}
```

What's different about Terraform?

State-FUL

- Checks the current configuration before making changes to help avoid any potential conflicts
- Quick to remove config, no need to create a separate file

```
$ terraform destroy
```

Use Case Examples



Terraform for Model Driven Telemetry

Enable gRPC Dial-Out telemetry subscriptions for the POE and Basic Device Monitoring use cases

```
aut@pod22-xelab:~/mdl_examples$ terraform plan -var-file="var.tfvars"
Terraform used the selected providers to generate the following execution plan. Resource actions are indicated with the following symbols:
+ create

Terraform will perform the following actions:

# iosxe_mdt_subscription.cpu_subs["100"] will be created
+ resource "iosxe_mdt_subscription" "cpu_subs" {
+   encoding      = "encode-kvgpb"
+   filter_xpath  = "/process-cpu-ios-xe-oper:cpu-usage/cpu-utilization/five-seconds"
+   id            = (known after apply)
+   receivers     = [
+     {
+       address = "10.1.1.3"
+       port   = 57500
+       protocol = "grpc-tcp"
+     },
+   ]
+   stream       = "yang-push"
+   subscription_id = 100
+   update_policy_periodic = 3000
}

# iosxe_mdt_subscription.cpu_subs["101"] will be created
+ resource "iosxe_mdt_subscription" "cpu_subs" {
+   encoding      = "encode-kvgpb"
+   filter_xpath  = "/process-cpu-ios-xe-oper:cpu-usage/cpu-utilization/one-minute"
+   id            = (known after apply)
+   receivers     = [
+     {
+       address = "10.1.1.3"
+       port   = 57500
+       protocol = "grpc-tcp"
+     },
+   ]
+   stream       = "yang-push"
+   subscription_id = 101
+   update_policy_periodic = 3000
}
```

Lab Guide Steps:

1. Introduction
2. IOS XE CLI pre-req
3. Terraform Install & headers, device variables
4. Variables and config for MDT subscription
5. Terraform configuration for device monitoring
6. TF Workflow: init, plan, apply & destroy
7. Validation with TF and CLI
8. Conclusion

https://registry.terraform.io/providers/CiscoDevNet/iosxe/latest/docs/resources/mdt_subscription
https://registry.terraform.io/providers/CiscoDevNet/iosxe/latest/docs/data-sources/mdt_subscription
<https://github.com/jeremycohoe/cisco-ios-xe-panda-lab-terraform>

iosxe_mdt_subscription (Resource)

This resource can manage the MDT Subscription configuration.

Example Usage

```
resource "iosxe_mdt_subscription" "example" {
  subscription_id = 101
  stream         = "yang-notif-native"
  encoding       = "encode-kvgpb"
  source_vrf     = "Mgmt-vrf"
  source_address = "1.2.3.4"
  update_policy_on_change = true
  filter_xpath   = "/ios-events-ios-xe-oper"
  receivers = [
    {
      address = "5.6.7.8"
      port   = 57600
      protocol = "grpc-tcp"
    }
  ]
}
```

Use the Docker Container with the Terraform files included!

1. Ensure Docker is installed
2. Run the following commands
 1. `docker pull jeremycohoe/tig_mdt`
 2. `docker run -ti -p 3000:3000 -p 57500:57500 jeremycohoe/tig_mdt`
3. Identify the container ID
 1. `docker ps`

```
sdeweese@SDEWEESE-M-C20V ~ % docker ps
```

CONTAINER ID	IMAGE	COMMAND	CREATED	STATUS	PORTS	NAMES
288Fa40Fd38b	jeremycohoe/tig_mdt	"/start -d"	43 seconds ago	Up 42 seconds	0.0.0.0:3000->3000/tcp, 0.0.0.0:57500->57500/tcp	inspiring_gould

4. Enter into the container
 1. `docker exec -it CONTAINER_ID /bin/bash`
 1. Note: replace `CONTAINER_ID` with the ID found in step 3

5. Navigate to the correct folder

1. `cd`
2. `cd cisco-ios-xe-panda-lab-terraform`

6. Modify the device credentials in the header.tf file

```
provider "iosxe" {  
    username = "admin" ← replace with Cisco IOS XE device username  
    password = "XXXXXXXX" ← replace with Cisco IOS XE device password  
    url = "https://your-switch-hostname-or-ip" ← replace with Cisco IOS XE device hostname or IP  
}
```

7. Configure the Cisco IOS XE device using Terraform

```
sdeweese@SDEWEESE-M-C20V ~ % docker exec -it 288fa40fd38b /bin/bash  
root@288fa40fd38b:~/# cd  
root@288fa40fd38b:~/# ls  
cisco-ios-xe-panda-lab-terraform start.sh  
root@288fa40fd38b:~/# cd cisco-ios-xe-panda-lab-terraform  
root@288fa40fd38b:~/cisco-ios-xe-panda-lab-terraform#  
root@288fa40fd38b:~/cisco-ios-xe-panda-lab-terraform#  
root@288fa40fd38b:~/cisco-ios-xe-panda-lab-terraform# ls  
README.md cpu.tf header.tf imgs terraform.tfstate terraform.tfstate.backup terraform.tfvars xpaths.tf
```


Example TF file

```
1 terraform {
2   required_providers {
3     iosxe = {
4       source = "CiscoDevNet/iosxe"
5       version = ">= 0.5.1"
6     }
7   }
8 }
9
10 provider "iosxe" {
11   username = "developer"
12   password = "Cisco12345"
13   url      = "https://198.18.1.21"
14 }
15
16 variable source_address {
17   type = string
18   default = "1.1.1.1"
19   description = "Source address"
20 }
21
22 variable receiver_ip {
23   type = string
24   default = "1.1.1.1"
25   description = "Receiver IP"
26 }
27
28 variable receiver_port {
29   type = string
30   default = "57500"
31   description = "Port to send data to"
32 }
33
34 resource "iosxe_mdt_subscription" "cpu_subs" {
35   for_each = var.cpu_subscriptions
36   subscription_id = each.key
37   stream = "yang-push"
38   encoding = "encode-kvgpb"
39   source_vrf = "Mgmt-vrf"
40   update_policy_periodic = var.cpu_periodic
41   source_address = var.source_address
42   filter_xpath = each.value.xpath
43   receivers = [
44     {
45       address = var.receiver_ip
46       port = var.receiver_port
47       protocol = "grpc-tcp"
48     }
49   ]
50 }
51
52 variable cpu_periodic {
53   type = string
54   default = "100"
55   description = "Short update interval"
56 }
57
58 #CPU.tf
59 variable "cpu_subscriptions" {
60   default = {
61     100 = {
62       xpath = "/process-cpu-ios-xe-oper:cpu-usage/cpu-utilization/five-seconds"
63     },
64     101 = {
65       xpath = "/process-cpu-ios-xe-oper:cpu-usage/cpu-utilization/one-minute"
66     },
67     102 = {
68       xpath = "/process-cpu-ios-xe-oper:cpu-usage/cpu-utilization/five-minutes"
69     }
70   }
71 }
```

Creates three MDT subscriptions for various CPU data

<https://github.com/jeremycohoe/cisco-ios-xe-dcloud-terraform/tree/main>

DEMO – install docker container and use Terraform files to configure telemetry subscriptions



```
auto@pod27-xelab: ~  
auto@pod27-xelab: ~$  
auto@pod27-xelab: ~$ docker images  
REPOSITORY TAG IMAGE ID CREATED SIZE  
auto@pod27-xelab: ~$  
auto@pod27-xelab: ~$ docker ps  
CONTAINER ID IMAGE COMMAND CREATED STATUS PORTS NAMES  
auto@pod27-xelab: ~$  
auto@pod27-xelab: ~$  
c9300-pod27# sh run | s tel  
telemetry ietf subscription 6041337  
encoding encode-kvgpb  
filter xpath /process-cpu-ios-xe-oper:cpu-usage/cpu-utilization/five-seconds  
stream yang-push  
update-policy periodic 30000  
receiver ip address 10.1.1.3 57500 protocol grpc-tcp  
c9300-pod27#  
c9300-pod27#  
Oct 16 21:55:56.082: %HA_EM-6-LOG: catchall: show running-config
```

IPsec tunnel + cloud automation with Terraform

Day 0




YouTube video coming soon!

1. Terraform configures the IPsec tunnel between the 9300X and the cloud service where the internal resources are available
2. Terraform also manages the cloud-native resources including certificate key management and IP subnetting
3. Connections between VPC, VPN, CGW and device certificates, tunnels, and interfaces are created


1. Virtual Private Cloud (VPC)
2. Virtual Private Network (VPN)
3. Customer Gateway (CGW)

1. Tunnel
2. Proposal
3. Policy
4. Keyring
5. Profile
6. IPSEC Transform
7. IPSEC Profile
8. Tunnel Interface




IPsec Tunnel for employees

Day 1



YouTube video coming soon!



<https://github.com/sdeweese/terraform-ipsec-tunnel-to-cloud>


Resources



Blog and Resources: Terraform

<https://github.com/CiscoDevNet/terraform-provider-iosxe/>
<https://registry.terraform.io/search/providers?namespace=CiscoDevNet>

Questions? Join the Ask
IOS XE Terraform Provider
Webex space:
<https://eurl.io/#PtsT8eJFI>




Demo Create a Crypto Tunnel Video:

<https://www.youtube.com/watch?v=bPS0bhPacDw>

Intro to IOS XE Terraform Provider Video:

https://www.youtube.com/watch?v=GEY_hyXimbA



Crypto IPsec Live Stream with DevRel:

<https://www.youtube.com/watch?v=WkgDIE0HpXs>




Developer

Automation with Any Tooling on Any
Interface

Story DeWeese

Terraform expands into the extensive Cisco IOS XE
programmability and automation ecosystem



IOS XE's vast, programmable feature set

The Cisco IOS XE ecosystem is programmatically managed and supports a variety of tooling. This includes Ansible to YANG Suite, pyATS over NETCONF, RESTCONF, gNMI, and even with legacy CLIs. With the addition of the new Cisco IOS XE Terraform provider, we add an additional tool into the IOS XE configuration management toolbox.

<https://blogs.cisco.com/developer/terraformiosxe01>

dCloud Programmability

<https://dcloud.cisco.com>

“Cisco Catalyst 9000 IOS XE Programmability & Automation Lab v1”

<https://dcloud2.cisco.com/demo/catalyst-9000-ios-xe-programmability-automation-lab-v1>

Use Cases:

EVPN:

Ansible with CLI deployment of EVPN solutions
 EVPN management over RESTCONF/YANG with Postman
 Declarative EVPN fabric management with Terraform

Model Driven Telemetry

Telemetry configuration with CLI and YANG Suite
 Collection with TIG_MDT container and tooling

YANG Programmability

YANG Suite tooling and integrations to YANG API's
 Ansible integrations

Tooling and Integrations

YANG Suite

- NETCONF/RESTCONF/gNMI API
 - Ansible integration
- NETCONF/gNMI Dial-In Telemetry
- gRPC Dial-Out Telemetry receiver

Telemetry

- TIG stack in Docker
- Grafana dashboard for device health

Postman / RESTCONF

- EVPN fabric API calls

Terraform/RESTCONF

- Declarative EVPN fabric management

Ansible

- EVPN solution enablement using CLI





Ubuntu VM Details:

Syslog receiver from all switches
 TFTP config backup
 See slide

Windows VM Details

VS Code Terraform @ folder
 Ansible @ folder
 Chrome browser YANG Suite, Grafana
 Bash/PS/Cmd shells SSH into C9K or Ubuntu
 Postman Workspace for EVPN

3x C9K Virtual VM's



Cisco Catalyst IOS XE Programmability Sessions at Cisco Live Europe Amsterdam 2024

Monday Feb 5

11AM **DEVLIT-2083:**
Automate Cisco IOS XE Device Configuration Using Terraform (Story)

1:30PM **CISCOU-1024:**
Model Driven Telemetry with Cisco IOS XE made Simple (Jeremy)

3:30PM **DEVLIT-1965:**
Automation using multiple API's in the IOS XE Device Programmability Lab (Jeremy)

Session Levels:
Beginner
Intermediate

Tuesday Feb 6

11:30AM **DEVNET-1441:**
Catalyst 9000 Virtual topology simulation and configuration management solutions (Ama+Jeremy)

11:30AM **DEVLIT-2787:**
Explore and visualize YANG models with YANG Suite (Story)

1:30PM **DEVVKS-2270:**
Implementing Cisco IOS XE Model Driven Telemetry with Telegraf, InfluxDB, and Grafana (Jeremy)

1:30PM **CISCOU-2013:**
Explore Cisco IOS XE Automation Tooling and Use Cases (Story)

4:30PM **DEVLIT-2062:**
Getting Started with Secure Zero Touch Provisioning (Story)

Wednesday Feb 7

1:30PM **DEVNET-2464:**
How to Become a Cisco IOS XE Terraform Expert (Story)

4:30PM **CISCOU-2021:**
gNMI Oh My! Automation with the gRPC micro-services on IOS XE (Jeremy)

Thursday Feb 8

2:30PM **BRKOPS-2455:**
Infrastructure as Code with Cisco Catalyst 9000 Virtual (Ama+Jeremy)

2:30PM **DEVNET-1468:**
Programmability, Automation Model Driven Telemetry on Cisco IOS XE with a dash of YANG Suite (Story)


Friday Feb 9



Learn more about sessions this week and on-demand:
<https://blogs.cisco.com/developer/osxeciscoliveemea2024>

Cisco DevNet Site

The one-stop-shop for Cisco IOS XE Programmability resources including videos, white papers, labs and more!



The screenshot shows the Cisco DevNet website interface. At the top, there is a navigation bar with 'cisco DevNet' logo, 'Documentation', 'Learn', 'Technologies', 'Community', and 'Events'. A search icon and 'SIGN UP FREE' button are also present. Below the navigation bar, the breadcrumb trail reads 'Technology > Networking > IOS XE'. The main content area features a dark blue header with the title 'Cisco IOS XE Programmability and Automation' and a sub-header: 'Cisco IOS XE programmability and automation enables network operators and developers an alternative approach to CLI for device configuration, management and telemetry at scale.' A 'Read the docs' button is centered below the sub-header. A carousel of three featured items is shown: 'LIVE STREAM: Terraform + IOS XE | A Match Made on the Internet', 'WEBINAR: Automating Catalyst IOS XE', and 'WHITE PAPER: Catalyst Programmability and Automation'. Below the carousel, the section 'Programmability options with IOS XE' is divided into two columns. The left column, 'Provisioning', includes an icon of a network diagram and text about Day 0 provisioning automation features like ZTP and PXE. The right column, 'Configuration management', includes an icon of a document and text about programmatic configuration options for Catalyst hardware, mentioning CLI, SNMP, and WebUI.




<https://developer.cisco.com/iosxe/>

API White Paper

Products & Services / Switches / Campus LAN Switches - Access / Cisco Catalyst 9300 Series Switches /

Catalyst Programmability and Automation



Website: <https://www.cisco.com/c/en/us/products/collateral/switches/catalyst-9300-series-switches/nb-06-catalyst-programmability-automation-wp.html>

PDF: <https://www.cisco.com/c/en/us/products/collateral/switches/catalyst-9300-series-switches/nb-06-catalyst-programmability-automation-wp.pdf>

Webinar with live demos & examples: <https://www.youtube.com/watch?v=Ldck5PnPu2I>

<http://cs.co/apiwp>



<http://cs.co/apiwppdf>

Programmability and auto... ^



Table of Contents

Programmability and automatio... -

Day 0: Provisioning automation

Day 1: Model-driven programmability

Day 2: Model-driven telemetry

Day N: Device optimization

Cisco IOS XE operational consistency

Yet Another Next Generation (Y...+)

Day 1: Model-driven program... +

Tooling: Cisco YANG Suite +

Day 2: Model-driven telemetry +

Day N: Device optimization +

Conclusion

Additional resources +

Blogs

Cisco Programmability on YouTube

<https://www.youtube.com/jeremycohoe1>

<https://www.youtube.com/ciscoenprogrammability>

<https://www.youtube.com/ciscocatalysttv>

Uploads ▶ Play all



Using PowerShell and PowerCLI to create 10 clones... 280 views • 2 years ago

Getting started with Cisco YANG Suite 5K views • 2 years ago

Cisco Catalyst IOS XE - gNMI gNOI cert.proto - quick dem... 265 views • 2 years ago

Cisco IOS XE gRPC Model-Driven Telemetry (MDT) wit... 1.8K views • 2 years ago

IPXE - Cisco IOS XE Programmability and... 851 views • 2 years ago

Cisco Catalyst IOS XE 9300 demo of the NETCONF API L... 1.2K views • 3 years ago

HOME VIDEOS PLAYLISTS COMMUNITY CHANNELS ABOUT 🔍

Videos ▶ Play all



Cisco IOS XE Programmability and... 64 views • 1 month ago

Cisco YANG Suite release 3 35 views • 5 months ago

NETCONF with YANG Suite 117 views • 1 year ago

Cisco IOS XE Terraform provider introduction and... 177 views • 1 year ago

Cisco Catalyst 9300 IOS XE 17.5 GNM1 GNOI OS.proto ... 225 views • 2 years ago

Cisco DNA Center Client Proximity API and Event Use Case 157 views • 2 years ago

HOME VIDEOS PLAYLISTS COMMUNITY CHANNELS ABOUT 🔍

Cisco Catalyst TV
@CiscoCatalystTV 1.63K subscribers 74 videos
Welcome to Cisco Catalyst TV! This channel is all about Cisco Catalyst Pla... >

HOME VIDEOS PLAYLISTS COMMUNITY CHANNELS ABOUT 🔍

Subscribed ▾

Videos ▶ Play all



URL Filtering on Catalyst 8000V 28 views • 3 days ago

Catalyst PoE High Availability 81 views • 2 weeks ago

Introducing Catalyst 9500X 60L4D Campus Core 52 views • 2 weeks ago

Introducing the Catalyst 9200CX Series Switches 348 views • 1 month ago

IOS XE 17.11.1 Catalyst Switching Highlights 219 views • 1 month ago

IOS-XE Power Telemetry and Automation 188 views • 2 months ago

Catalyst Switching ▶ Play all



Cloud Security on Catalyst 9000 300 views • 2 years ago

Application Hosting with Catalyst 9000 Demo 465 views • 2 years ago

CW Precision Timing PTPv2 IEEE1588-2008 490 views • 2 years ago

Cisco UP0E+ and POE Analytics 340 views • 2 years ago

Encrypted Traffic Analytics 242 views • 2 years ago

ThousandEyes with Catalyst 9000 Switching - Overview 928 views • 1 year ago

Cisco U modules

- ZTP:
<https://ondemandlearning.cisco.com/apollo-alpha/tc-iosxe-ztp/pages/1>
- Terraform:
<https://ondemandlearning.cisco.com/apollo-alpha/tc-terraform-ios-xe/pages/1>
- YANG Suite + NETCONF:
<https://ondemandlearning.cisco.com/apollo-alpha/tc-yangsuite-netconf/pages/1>
- YANG Suite + RESTCONF:
<https://ondemandlearning.cisco.com/apollo-alpha/tc-yangsuite-restconf/pages/1>

The screenshot shows a web page titled "Overview" for the "Cisco IOS XE Terraform Provider" module. The page is part of a learning path that is 25% complete. The navigation menu on the right includes "Overview" (selected), "Introduction to Terraform", "Create and Apply the Terraform...", and "Congratulations". The main content area is titled "Overview" and includes a "Return" button. Under "What You'll Learn", it lists three bullet points: "How to apply the Cisco IOS XE Terraform provider", "How to create a VLAN using the Cisco IOS XE Terraform provider", and "How to verify that the Terraform execution plan file was successfully applied to a Cisco IOS XE device". Under "What You'll Need", it lists two bullet points: "Terraform and the Cisco IOS XE provider installed on a host that will apply changes to the device. See how to install Terraform." and "Access to a Sandbox (such as the DevNet IOS XE Sandbox)". A note at the bottom states: "Alternatively, if you have access to dCloud, you can use it here; lab name 'Cisco Catalyst 9000 IOS XE Programmability & Automation Lab v1'". At the bottom of the page, there is a blue banner with the text "Keep going!" and a button labeled "Next: Introduction to Terraform →".

Continue to Learn, Code and Build with Cisco DevNet!

Get access to an exclusive learning module filled with digital learning opportunities on topics including **Cisco Networking** and more.

Scan QR Code to get started.





The bridge to possible

Thank you

CISCO *Live!*

The Cisco Live! logo features the word "CISCO" in a bold, black, sans-serif font, followed by "Live!" in a black, cursive script font. The background of the entire image is a vibrant, multi-colored abstract pattern of overlapping, wavy bands in shades of red, orange, yellow, green, and blue, creating a sense of motion and energy.

CISCO *Live!*

Let's go